

AGRITRAK

TRACTOR BANDEN. DE VOORDELEN VAN
LUCHTBANDEN EN RUBBEREN RUPS BANDEN



420/84R38CW TECHNISCHE GEGEVENS

									
MAAT	RIM	APP. RIMS	LADEN INDEX	GELADEN STATISCHE RADIO	LOOPVLAK TYPE	TREEDDIEPTE	SW	OD	RC
				mm		mm	mm	mm	mm
				in		1/32	in	in	in
420/85R38CW	DW15L	DW14L	149D	740	R-1W	49	446	1672	4920
				29.1		62	17.6	65.8	193.7

MAAT	INFLATIED RUK	SNELHEID, KM/H, MPH				
		AANBEVOLEN BELASTING, KG/LB				
	bar	10	25	30	40	50
	psi	6	16	19	25	31
420/85R38CW	0.6	2080	1840	1780	1660	1660
	0.8	2590	2300	2210	2070	2070
	12	5700	5070	4870	4560	4560
	1.0	3050	2710	2610	2440	2440
	15	6720	5970	5750	5370	5370
	1.2	3500	3110	3000	2800	2800

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

ONZE VOORDELEN



SUPERIOR
FLOTATIE



VERMINDERDE
BODEM
SAMENSTELLING



VERHOOGDE
TRACTIE



RUNDFLAT
MOGELIJKHEDEN



DUURZAAMHEID
VAN DE
ZIJWANDEN



ZELF
REINIGEN



GELIJKMATIGE
VERDELING VAN
DE BELASTING