

AGRITRAK



TRACTOR TIRES. THE ADVANTAGES OF PNEUMATIC TIRES & RUBBER TRACKS

420/84R38CW TECHNICAL DATA SHEET

SIZE	RIM	APP. RIMS	LOAD INDEX	LOADED STATIC RADIUS	TREAD TYPE	TREAD DEPTH	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	
				in		1/32	in	in	
420/85R38CW	DW15L	DW14L	149D	740	R-1W	49	446	1672	4920
				29.1		62	17.6	65.8	193.7

SIZE	INFLATION PRESSURE	SPEED, KM/H (MPH)				
		RECOMMENDED LOAD KG / LB				
	bar	10	25	30	40	50
420/85R38CW	psi	6	16	19	25	31
	0.6	2080	1840	1780	1660	1660
	0.8	2590	2300	2210	2070	2070
	12	5700	5070	4870	4560	4560
	1.0	3050	2710	2610	2440	2440
	15	6720	5970	5750	5370	5370
	1.2	3500	3110	3000	2800	2800
17	7710	6850	6610	6170	6170	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

OUR BENEFITS



SUPERIOR FLOTATION



INCREASED TRACTION



REDUCED SOIL COMPACTION



SIDEWALL DURABILITY



RAN FLAT CAPABILITIES



SELF CLEANING



UNIFORM LOAD DISTRIBUTION