

AGRICUP

DIE IDEALE PNEUMATISCHE
LÖSUNG FÜR LANDMASCHINEN



480/70R34CW TECHNISCHE DATEN

									
GRÖSSE	RIM	APP. RIMS	LAST INDEX	STATISCHER RADIUS	FELGENART	FELGENTIEFE	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	mm
				in		1/32	in	in	in
480/70R34CW	DW15L	W15L W/DW14L W/DW-16L	143D	700	R-1W+	56	485	1599	4688
				27.5		71	19.8	65.3	184.6

GRÖSSE	FÜLLDRUCK	GESCHWINDIGKEIT, KM/H (MPH)					
		EMPFOHLENE LAST KG / LB					
	bar	10	25	30	40	50	65
	psi	6	16	19	25	31	40
480/70R34CW	0.6	2730	2160	2100	2000	1920	1820
	8.7	6020	4770	4630	4410	4240	4020
	0.8	3230	2550	2480	2360	2260	2150
	11.6	7130	5630	5470	5210	4990	4740
	1.0	3680	2910	2820	2690	2580	2450
	14.5	8120	6420	6220	5940	5690	5410
	1.2	4090	3230	3140	2990	2870	2725
	17.4	9020	7130	6930	6600	6330	6010

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

UNSERE VORTEILE



HOCHWERTIGE
FLOTATION



ERHÖHTE
TRAKTION



RUHIGERES
FAHRVERHALTEN



EXTRA
LANGLEBIG



NOTLAUF
TAUGLICHKEIT



ERWEITERTER
LASTINDEX



SELBSTREINIGEND