

# AGRICUP

TRACTOR BANDEN. DE VOORDELEN VAN  
LUCHTBANDEN EN RUBBEREN RUPS BANDEN



## 420/84R38CW TECHNISCHE GEGEVENS

MAAT	RIM	APP. RIMS	LADEN INDEX	GELADEN STATISCHE RADIO	LOOPVLAK TYPE	TREEDDIEPTE	SW	OD	RC
				mm		mm	mm	mm	
				in		1/32	in	in	
420/85R38CW	DW15L	W13 DW14L	144A8	740	R-1W	49	446	1672	4920
				29.1		62	17.6	65.8	193.7

MAAT	INFLATIED RUK	SNELHEID, KM/H, MPH				
		AANBEVOLEN BELASTING, KG/LB				
		10	25	30	40	50
420/85R38CW	bar	6	16	19	25	31
	psi	2080	1840	1780	1660	1660
	0.6	2590	2300	2210	2070	2070
	0.8	5700	5070	4870	4560	4560
	1.0	3050	2710	2610	2440	2440
	1.2	6720	5970	5750	5370	5370
		3500	3110	3000	2800	2800

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

## ONZE VOORDELEN



SUPERIOR  
FLOTATIE



VERMINDERDE  
BODEM  
SAMENSTELLING



VERHOOGDE  
TRACTIE



RUNDFLAT  
MOGELIJKHEDEN



DUURZAAMHEID  
VAN DE  
ZIJWANDEN



ZELF  
REINIGEN



GELIJKMATIGE  
VERDELING VAN  
DE BELASTING