

AGRICUP



TRACTOR TIRES. THE ADVANTAGES
OF PNEUMATIC TIRES & RUBBER TRACKS

710/70R38CW TECHNICAL DATA SHEET

SIZE	RIM	APP. RIMS	LOAD INDEX	LOADED STATIC RADIUS	TREAD TYPE	TREAD DEPTH	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	
				in		1/32	in	in	
710/70R38CW	DW23B	DW25B	166D	850	R-1W	60	760	1940	5749
				33.5		76	299	76.4	226.3

SIZE	INFLATION PRESSURE	SPEED, KM/H (MPH)									
		RECOMMENDED LOAD KG / LB									
		40	10	15	20	25	30	40	50	65	70
	bar	Dual	6	9	12	16	19	25	31	40	44
710/70R38CW	0.4	2670	4170	3730	3420	3290	3200				
	6	5880	9190	8220	7530	7250	7050				
	0.6	3390	5300	4730	4340	4180	4060	3870	3710		
	9	7470	11670	10420	9560	9210	8940	8520	8170		
	0.8	4010	6270	5600	5140	4950	4810	4580	4390	4180	3800
	12	8830	13810	12330	11320	10900	10590	10090	9670	9210	8370
	1.0	4570	7140	6380	5850	5640	5470	5210	5000	4760	4330
	15	10070	15730	14050	12890	12420	12050	11480	11010	10480	9540
	1.2	5090	7950	7100	6520	6280	6100	5800	5570	5300	4820
17	11210	17510	15640	14360	13830	13440	12780	12270	11670	10620	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

OUR BENEFITS



SUPERIOR FLOTATION



INCREASED TRACTION



REDUCED SOIL COMPACTION



SIDEWALL DURABILITY



RAN FLAT CAPABILITIES



SELF CLEANING



UNIFORM LOAD DISTRIBUTION