











AGRICUP

DIE IDEALE PNEUMATISCHE
LÖSUNG FÜR LANDMASCHINEN

GALILEO
CUPWHEEL

360/70R24CW TECHNISCHE DATEN

									
GRÖSSE	RIM	APP. RIMS	LAST INDEX	STATISCHER RADIUS	FELGENART	FELGENTIEFE	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	
				in		1/32	in	in	
360/70R24CW	DW11	DW10L	122D	510	R-1W+	48	335	1140	3400
				20.1		60	13.7	46.5	133.9

GRÖSSE	FÜLLDRUCK	GESCHWINDIGKEIT, KM/H (MPH)					
		EMPFOHLENE LAST KG / LB					
	bar	10	25	30	40	50	65
	psi	6	16	19	25	31	40
360/70R24CW	0.6	1500	1185	1150	1095	1050	1000
	8.7	3310	2620	3540	2420	2320	2210
	0.8	1785	1410	1369	1303	1250	1190
	11.6	3940	3110	3020	2880	2760	2630
	1.0	2025	1600	1553	1478	1420	1350
	14.5	4470	3530	3430	3260	3140	2980
	1.2	2250	1778	1725	1643	1580	1500
	17.4	4970	3920	3810	3630	3490	3310

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

UNSERE VORTEILE



HOCHWERTIGE
FLOTATION



ERHÖHTE
TRAKTION



RUHIGERES
FAHRVERHALTEN



EXTRA
LANGLEBIG



NOTLAUF
TAUGLICHKEIT



ERWEITERTER
LASTINDEX



SELBSTREINIGEND