

# AGRICUP

TRACTOR BANDEN. DE VOORDELEN VAN  
LUCHTBANDEN EN RUBBEREN RUPS BANDEN



## 360/70R24CW TECHNISCHE GEGEVENS

MAAT	RIM	APP. RIMS	LADEN INDEX	GELADEN STATISCHE RADIO	LOOPVLAK TYPE	TREEDDIEPTE	SW	OD	RC
				mm		mm	mm	mm	
				in		1/32	in	in	
360/70R24CW	DW11	DW10L	122D	510	R-1W	48	335	1140	3400
				20.1		60	13.7	46.5	133.9

MAAT	INFLATIED RUK	SNELHEID, KM/H, MPH					
		AANBEVOLEN BELASTING, KG/LB					
	bar	10	25	30	40	50	65
	psi	6	16	19	25	31	40
360/70R24CW	0.6	1500	1185	1150	1095	1050	1000
	8.7	3310	2620	3540	2420	2320	2210
	0.8	1785	1410	1369	1303	1250	1190
	11.6	3940	3110	3020	2880	2760	2630
	1.0	2025	1600	1553	1478	1420	1350
	14.5	4470	3530	3430	3260	3140	2980
	1.2	2250	1778	1725	1643	1580	1500
17.4	4970	3920	3810	3630	3490	3310	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

## ONZE VOORDELEN



SUPERIOR  
FLOTATIE



VERMINDERDE  
BODEM  
SAMENSTELLING



VERHOOGDE  
TRACTIE



RUNDFLAT  
MOGELIJKHEDEN



DUURZAAMHEID  
VAN DE  
ZIJWANDEN



ZELF  
REINIGEN



GELIJKMATIGE  
VERDELING VAN  
DE BELASTING