

# AGRICUP



TRACTOR TIRES. THE ADVANTAGES  
OF PNEUMATIC TIRES & RUBBER TRACKS

## 600/65R28CW TECHNICAL DATA SHEET

SIZE	RIM	APP. RIMS	LOAD INDEX	LOADED STATIC RADIUS	TREAD TYPE	TREAD DEPTH	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	
				in		1/32	in	in	
600/65R28CW	DW20B	W18L DW18L DW21B	154D	655	R-1W	50	597	1484	4405
				25.8		63	23.5	58.4	173.4

SIZE	INFLATION PRESSURE	SPEED, KM/H, MPH									
		RECOMMENDED LOAD KG / LB									
		bar	40	10	15	20	25	30	40	50	65
	psi	Dual	6	9	12	16	19	25	31	40	44
600/65R28CW	0.4	1890	2960	2640	2420	2330	2270				
	6	4160	6520	5810	5330	5130	5000				
	0.6	2400	3750	3350	3080	2960	2880	2740	2630	2500	
	9	5290	8260	7380	6780	6520	6340	6040	5790	5510	
	0.8	2840	4440	3970	3640	3510	3400	3240	3110	2960	2690
	12	6260	9780	8740	8020	7730	7490	7140	6850	6520	5930
	1.0	3240	5060	4520	4150	3990	3880	3690	3540	3370	3070
	15	7140	11150	9960	9140	8790	8550	8130	7800	7420	6760
	1.2	3600	5630	5030	4610	4440	4310	4110	3940	3750	3410
17	7930	12400	11080	10150	9780	9490	9050	8680	8260	7510	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

### OUR BENEFITS



SUPERIOR FLOTATION



INCREASED TRACTION



REDUCED SOIL COMPACTION



SIDEWALL DURABILITY



RAN FLAT CAPABILITIES



UNIFORM LOAD DISTRIBUTION



SELF CLEANING