











# AGRICUP

農業機械に最適なソリューションを提供します。



## 600/65R28CW テクニカルデータ

									
タイヤサイズ	推奨リム幅	適用リム幅	LI/SS	静荷重半径	TRAコード	TREAD DEPTH	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	mm
				in		1/32	in	in	in
600/65R28CW	DW20B	W18L	154D	655	R-1W	50	597	1484	4405
		DW18L DW21B		25.8		63	23.5	58.4	173.4

タイヤサイズ	空気圧	最大速度									
		最大荷重									
	bar	40	10	15	20	25	30	40	50	65	70
	psi	Dual	6	9	12	16	19	25	31	40	44
600/65R28CW	0.4	1890	2960	2640	2420	2330	2270				
	6	4160	6520	5810	5330	5130	5000				
	0.6	2400	3750	3350	3080	2960	2880	2740	2630	2500	
	9	5290	8260	7380	6780	6520	6340	6040	5790	5510	
	0.8	2840	4440	3970	3640	3510	3400	3240	3110	2960	2690
	12	6260	9780	8740	8020	7730	7490	7140	6850	6520	5930
	1.0	3240	5060	4520	4150	3990	3880	3690	3540	3370	3070
	15	7140	11150	9960	9140	8790	8550	8130	7800	7420	6760
	1.2	3600	5630	5030	4610	4440	4310	4110	3940	3750	3410
	17	7930	12400	11080	10150	9780	9490	9050	8680	8260	7510

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

## タイヤ特性



優れたフロー  
テーション



駆動力の  
向上



土壌圧縮  
抑制



タイヤ側面の  
耐久性の向上



ランフラット  
性能



セルフクリー  
ニング



荷重の均一  
な分散