











AGRICUP

DIE IDEALE PNEUMATISCHE
LÖSUNG FÜR LANDMASCHINEN

GALILEO
CUPWHEEL

420/84R38CW TECHNISCHE DATEN

									
GRÖSSE	RIM	APP. RIMS	LAST INDEX	STATISCHER RADIUS	FELGENART	FELGENTIEFE	SW	OD	ROLLING CIRC.
				mm		mm	mm	mm	
				in		1/32	in	in	in
420/85R38CW	DW15L	W13 DW14L	144A8	740	R-1W	49	446	1672	4920
				29.1		62	17.6	65.8	193.7

GRÖSSE	FÜLLDRUCK	GESCHWINDIGKEIT, KM/H (MPH)				
		EMPFOHLENE LAST KG / LB				
	bar	10	25	30	40	50
	psi	6	16	19	25	31
420/85R38CW	0.6	2080	1840	1780	1660	1660
	0.8	2590	2300	2210	2070	2070
	12	5700	5070	4870	4560	4560
	1.0	3050	2710	2610	2440	2440
	15	6720	5970	5750	5370	5370
	1.2	3500	3110	3000	2800	2800
	17	7710	6850	6610	6170	6170

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

UNSERE VORTEILE



HOCHWERTIGE
FLOTATION



ERHÖHTE
TRAKTION



RUHIGERES
FAHRVERHALTEN



EXTRA
LANGLEBIG



NOTLAUF
TAUGLICHKEIT



ERWEITERTER
LASTINDEX



SELBSTREINIGEND