












AGRICUP



TRACTOR TIRES. THE ADVANTAGES
OF PNEUMATIC TIRES & RUBBER TRACKS

480/70R34CW TECHNICAL DATA SHEET

										
SIZE	RCOM. RIM	APP. RIMS	LOAD INDEX	TT/ TL /AL	TREAD TYPE	SW	OD	LOADED STATIC RADIUS	ROLLING CIRC.	TREAD DEPTH
						mm	mm	mm	mm	mm
						in	in	in	in	1/32
480/70R34CW	DW15 L	W15L	143D	TL	R-1W	485	1599	700	4688	56
		W/DW14L W/DW-16L				19.8	65.3	27.5	184.6	71

SIZE	INFLATION PRESSURE	SPEED, KM/H (MPH)					
		CONSTANT LOAD KG / LB					
		10	25	30	40	50	65
480/70R34CW	bar	10	25	30	40	50	65
	psi	6	16	19	25	31	40
	0.6	2730	2160	2100	2000	1920	1820
	8.7	6020	4770	4630	4410	4240	4020
	0.8	3230	2550	2480	2360	2260	2150
	11.6	7130	5630	5470	5210	4990	4740
	1.0	3680	2910	2820	2690	2580	2450
	14.5	8120	6420	6220	5940	5690	5410
1.2	4090	3230	3140	2990	2870	2725	
17.4	9020	7130	6930	6600	6330	6010	

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

OUR BENEFITS



SUPERIOR FLOTATION



INCREASED TRACTION



REDUCED SOIL COMPACTION



SIDEWALL DURABILITY



RAN FLAT CAPABILITIES



SELF CLEANING



UNIFORM LOAD DISTRIBUTION