












# AGRICUP



TRACTOR TIRES. THE ADVANTAGES  
OF PNEUMATIC TIRES & RUBBER TRACKS








## 360/70R24CW TECHNICAL DATA SHEET

										
SIZE	RCOM. RIM	APP. RIMS	LOAD INDEX	TT/ TL /AL	TREAD TYPE	SW	OD	LOADED STATIC RADIUS	ROLLING CIRC.	TREAD DEPTH
						mm	mm	mm	mm	mm
						in	in	in	in	1/32
360/70R24CW	DW11	DW10L	122D	TL	R-1W	335	1140	510	3400	48
						13.7	46.5	20.1	133.9	60

SIZE	INFLATION PRESSURE	SPEED, KM/H (MPH)					
		CONSTANT LOAD KG / LB					
		10	25	30	40	50	65
	bar	10	25	30	40	50	65
	psi	6	16	19	25	31	40
360/70R24CW	0.6	1500	1185	1150	1095	1050	1000
	8.7	3310	2620	3540	2420	2320	2210
	0.8	1785	1410	1369	1303	1250	1190
	11.6	3940	3110	3020	2880	2760	2630
	1.0	2025	1600	1553	1478	1420	1350
	14.5	4470	3530	3430	3260	3140	2980
	1.2	2250	1778	1725	1643	1580	1500
	17.4	4970	3920	3810	3630	3490	3310

GALILEOWHEEL.COM // INFO@GALILEOWHEEL.COM

### OUR BENEFITS

-  SUPERIOR FLOTATION
-  INCREASED TRACTION
-  REDUCED SOIL COMPACTION
-  SIDEWALL DURABILITY
-  RAN FLAT CAPABILITIES
-  SELF CLEANING
-  UNIFORM LOAD DISTRIBUTION